DATASHEET

# Epson Stylus Pro 7890



Designed with the print requirements of the commercial photography and fine art markets in mind, yet also representing a sound choice for the proofing market, the 24-inch Stylus Pro 7890 creates true-to-life prints at a high speed of up to 40m2/hour.

High quality colour: Achieve one of the highest colour gamuts available with consistently smooth gradations.

TFP print head: Tap into enhanced dot quality and crisp, clear images for betterthan-lab-quality prints.

UltraChrome K3 with Vivid Magenta inkset: Enjoy a superior range of naturallooking grey tones. Three densities of black - standard photo or matte black (selected automatically depending on the media) plus light black and light light black - create striking black and white output with a high contrast ratio, perfect tonal range and improved grey balance without colour casting.

Perfect colour: This combination of black inks means prints are free from bronzing, with a uniform surface appearance across both light and dark areas. Metamerism is also reduced, ensuring grey tones are consistent no matter what light source they are viewed under.

Boost productivity: Epson's Automatic Droplet Detection System fixes blocked nozzles without intervention. The printer also carries photo and matte black inks simultaneously, a built-in rotary knife cuts prints quickly and cleanly while paper rolls are changed effortlessly in seconds.

Optional inline SpectroProofer: Ensure consistent, repeatable colour accuracy when using different media, rapidly measuring control strips and colour charts when creating ICC profiles and print verification results.

## **KEY FEATURES**

- Large format 24-inch output
- Superior inks UltraChrome K3 with Vivid Magenta
- TFP print head Enhanced dot quality, crisp images
- High speed Print at up to 40m2/hour
- Boost productivity Automatic Droplet Detection System



## PRODUCT SPECIFICATIONS

PAPER / MEDIA HANDLING	
Paper Formats	A1, A2, A3+, A3, A4, B2, B3, B4, 17 " (43.2 cm), 24 " (61.0 cm), User defined
Print Margins Sheet Media	Mode 1: 3 mm (top), 3 mm (right), 14 mm (bottom), 3 mm (left)
Duplex	No
Compatible Paper Thickness	0.08 mm - 1.5 mm
Media Handling	Fine Art Paper Path, Roll Paper, Thick Media Support
TECHNOLOGY	
Printing Method	MicroPiezo TFP print head
Printing Resolution	2,880 x 1,440 dpi
Ink Technology	Ultrachrome® K3 Vivid Magenta
PRINT	
Maximum Printing Speed	162 sec/A1 on Matte paper
	360 Nozzles black, 360 Nozzles per colour
Nozzle Configuration	
Nozzle Configuration Colours	Light Black, Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid
-	
-	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid
Colours Minimum Droplet Size	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta
Colours Minimum Droplet Size	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl
Colours Minimum Droplet Size For detailed information on pr	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl
Colours Minimum Droplet Size For detailed information on pr CONNECTIVITY	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl inting speeds please visit http://www.epson.eu/testing.
Colours Minimum Droplet Size For detailed information on pr CONNECTIVITY Interfaces	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl inting speeds please visit http://www.epson.eu/testing.
Colours Minimum Droplet Size For detailed information on pr CONNECTIVITY Interfaces GENERAL	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl inting speeds please visit http://www.epson.eu/testing. USB, Ethernet
Colours Minimum Droplet Size For detailed information on pr CONNECTIVITY Interfaces GENERAL LCD screen	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl inting speeds please visit http://www.epson.eu/testing. USB, Ethernet Type: Color, Diagonal: 6.3 cm
Colours Minimum Droplet Size For detailed information on pr CONNECTIVITY Interfaces GENERAL LCD screen Energy Use	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl inting speeds please visit http://www.epson.eu/testing. USB, Ethernet Type: Color, Diagonal: 6.3 cm 70 W, 14 W (economy), 1 W (Power off)
Colours Minimum Droplet Size For detailed information on pr CONNECTIVITY Interfaces GENERAL LCD screen Energy Use Supply Voltage	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl inting speeds please visit http://www.epson.eu/testing. USB, Ethernet Type: Color, Diagonal: 6.3 cm 70 W, 14 W (economy), 1 W (Power off) AC 100 V - 240 V,50 Hz - 60 Hz
Colours Minimum Droplet Size For detailed information on pr CONNECTIVITY Interfaces GENERAL LCD screen Energy Use Supply Voltage Product dimensions	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl inting speeds please visit http://www.epson.eu/testing. USB, Ethernet Type: Color, Diagonal: 6.3 cm 70 W, 14 W (economy), 1 W (Power off) AC 100 V - 240 V,50 Hz - 60 Hz 1,356 x 667 x 1,218 mm (Width x Depth x Height)
Colours Minimum Droplet Size For detailed information on pr CONNECTIVITY Interfaces GENERAL LCD screen Energy Use Supply Voltage Product dimensions Product weight	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl inting speeds please visit http://www.epson.eu/testing. USB, Ethernet Type: Color, Diagonal: 6.3 cm 70 W, 14 W (economy), 1 W (Power off) AC 100 V - 240 V,50 Hz - 60 Hz 1,356 x 667 x 1,218 mm (Width x Depth x Height) 84.5 kg
Colours Minimum Droplet Size For detailed information on pr CONNECTIVITY Interfaces GENERAL LCD screen Energy Use Supply Voltage Product dimensions Product weight Included Software	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl inting speeds please visit http://www.epson.eu/testing. USB, Ethernet Type: Color, Diagonal: 6.3 cm 70 W, 14 W (economy), 1 W (Power off) AC 100 V - 240 V,50 Hz - 60 Hz 1,356 x 667 x 1,218 mm (Width x Depth x Height) 84.5 kg EpsonNet Config Mac OS 10.4+, Windows 2000, Windows 7, Windows 7 x64, Windows Server 2003 (32/64bit),
Colours Minimum Droplet Size For detailed information on pr CONNECTIVITY Interfaces GENERAL LCD screen Energy Use Supply Voltage Product dimensions Product weight Included Software Compatible Operating	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl inting speeds please visit http://www.epson.eu/testing. USB, Ethernet Type: Color, Diagonal: 6.3 cm 70 W, 14 W (economy), 1 W (Power off) AC 100 V - 240 V,50 Hz - 60 Hz 1,356 x 667 x 1,218 mm (Width x Depth x Height) 84.5 kg EpsonNet Config Mac OS 10.4+, Windows 2000, Windows 7, Windows 7 x64, Windows Server 2003 (32/64bit),
Colours Minimum Droplet Size For detailed information on pr CONNECTIVITY Interfaces GENERAL LCD screen Energy Use Supply Voltage Product dimensions Product weight Included Software Compatible Operating	Light Black, Light Light Black, Photo Black, Matte Black, Cyan, Light Cyan, Yellow, Vivid Magenta, Vivid Light Magenta 3.5 pl inting speeds please visit http://www.epson.eu/testing. USB, Ethernet Type: Color, Diagonal: 6.3 cm 70 W, 14 W (economy), 1 W (Power off) AC 100 V - 240 V,50 Hz - 60 Hz 1,356 x 667 x 1,218 mm (Width x Depth x Height) 84.5 kg EpsonNet Config Mac OS 10.4+, Windows 2000, Windows 7, Windows 7 x64, Windows Server 2003 (32/64bit), Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Vista, Windows Vista x64,

OTHER Warranty

12 months On site service Optional warranty extension available

#### LOGISTICS INFORMATION

SKU	C11CB51001A0
EAN code	8715946473543
Dimensions Single Carton	1530 x 795 x 955 mm
Carton Weight	148.28 Kg
Multiple Order Quantity	1 Units
Country of Origin	Japan
Pallet Size Euro	1 Units
Pallet Size Block	1 Units

Epson Stylus Pro 7890

## WHAT'S IN THE BOX

- Main unit
- Setup guide
- User manual (CD)
- Driver and utilities (CD)
- Warranty document
- Power cable
- Software (CD)

#### SUPPLIES

- Singlepack Photo Black T636100 UltraChrome HDR 700 ml C13T636100
- Singlepack Cyan T636200 UltraChrome HDR 700 ml C13T636200
- Singlepack Vivid Magenta T636300 UltraChrome HDR 700 ml C13T636300
- Singlepack Yellow T636400 UltraChrome HDR 700 ml
  - C13T636400
- Singlepack Light Cyan T636500 UltraChrome HDR 700 ml C13T636500
- Singlepack Vivid Light Magenta T636600 UltraChrome HDR 700 ml
  - C13T636600
- Singlepack Light Black T636700 UltraChrome HDR 700 ml
- C13T636700
- Singlepack Matte Black T636800 UltraChrome HDR 700 ml
- C13T636800
- Singlepack Light Light Black T636900 UltraChrome HDR 700 ml C13T636900
- Singlepack Photo Black T596100 UltraChrome HDR 350 ml
  - C13T596100
- Singlepack Cyan T596200 UltraChrome HDR 350 ml C13T596200
- Singlepack Vivid Magenta T596300 UltraChrome HDR 350 ml
- C13T596300
- Singlepack Yellow T596400 UltraChrome HDR 350 ml C13T596400

DIGG
Image: Second second

Web:

www.epson.co.uk

www.epson.ie

For more information please contact:

Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

